

|                                                                                   |            |                    |                        |
|-----------------------------------------------------------------------------------|------------|--------------------|------------------------|
|  | FRM-007    | Remplisseuse tubes | Fiche machine n°       |
|                                                                                   | Indice D   |                    | <b>DMC-STFSS<br/>A</b> |
|                                                                                   | Page 1 / 4 |                    | Version : 1.1          |

## Remplisseuse tubes

Fabricant : DMC

Modèle : DMC-STFSA

Précision de remplissage : +/- 1 %

Diamètre tube : 10 à 60 mm

Cadence : 50 à 70 pièces/minute

Chargement et positionnement automatiques des tubes

Écarteur de tube de pré-remplissage

Orientation automatique des tubes en lisant la marque à partir d'un capteur

Remplissage automatique avec doseur volumétrique

Trémie équipée de capteurs de niveau minimum et maximum, relié à la pompe de transfert

Système de soudage avec air chaud ou pliage spécifique pour tubes en aluminium

Encodage du lot avec système à pression

Dimensions hors tout (LxIxh) : 1700x1350x1680mm

## ***Tube filling machine***

*Manufacturer: DMC*

*Model: DMC-STFSA*

*Filling accuracy: +/- 1%*

*Tube diameter: 10 to 60 mm*

*Output: 50 to 70 units per minute*

*Automatic tube loading and positioning*

*Pre-filling tube spreader*

*Automatic tube orientation by reading the mark via a sensor*

*Automatic filling with volumetric dosing unit*

*Hopper fitted with minimum and maximum level sensors, connected to the transfer pump*

*Sealing system using hot air or a specialised folding method for aluminium tubes*

*Batch coding via a pressure-based system*

*Overall dimensions (LxWxH): 1700x1350x1680 mm*

# Remplisseuse tubes



## Remplisseuse tubes



## Remplisseuse tubes

