

	Fiche machine n°	<h1>Remplisseuse seringues</h1>	FRM-007
	5904		Indice A
	Indice A		Page 1 / 24

Remplisseuse seringues

Fabricant : Marchesini Tonazzi

Modèle : MI 120

Année : 2010

Pour produit visqueux

Non aseptique

Capacité de remplissage : 0,5 à 10 ml

3 formats installés : seringues diamètre 8 mm / hauteur 54-73 mm (voir fiche pdf)

Cadence max : 50 seringues/minute

Mode de fonctionnement :

- 1 Robot de chargement de seringue sur convoyeur d'entrée
- 1 Système de remplissage avec azote
- 1 Distribution de bouchon avec robot de dépose
- 1 Robot de déchargement

Interface Beckhoff

Panneau de commande Siemens Simatic Touch

Alimentation : 400 V 3-ph / 50 Hz / 15 A / 8 kW

Dimensionnel : voir document lay-out

Conforme normes CE

Documentation technique : disponible, détails sur demande

Incoterm : FCA

	Fiche machine n°	<h1>Remplisseuse seringues</h1>	FRM-007
	5904		Indice A
	Indice A		Page 2 / 24

Syringe filler

Manufacturer: Marchesini Tonazzi

Model: MI 120

Year: 2010

For viscous product

Non-aseptic

Filling capacity: 0,5 to 10 ml

3 installed formats: syringe diameter 8 mm / height 54-73 mm (see pdf file)

Max speed: 50 syringes/minute

Functioning:

1 syringes' loading robot on the infeed conveyor

1 nitrogen filling system

1 cap feeding system with robot

1 unloading robot

Beckhoff interface

Control panel: Siemens Simatic Touch

Power supply: 400 V 3-ph / 50 Hz / 15 A / 8 kW

Dimensions: see lay-out documenta attached

EC standards' compliant

Technical documentation: available, details on request

Incoterm: FCA











































